


iDISPLAY™ Tablet 27"

UIT427



The iDISPLAY Tablet 27" is designed as an freestanding or wall based interactive display. Operating on an Android operating system and powered by Pulse technology, this slim and elegant display includes all of the solutions needed for commercial locations. Attach to any standard TV/monitor VESA bracket and simply turn on the power. It is a fully interactive commercial display that uses capacitive touch, built in WiFi and LAN, and a host of integrated features that work in either landscape or portrait format. With the option to expand to 3G services*, this is an amazing, large screen interactive digital display that creates an engaging, memorable consumer experience.



*3G optional, pending carrier compatibility/availability.
For more information about iDISPLAY™ Tablets
please visit our website: www.outform.com/iDisplay-Tablets

OUTFORM™

Panel Information	Screen Size	27”
	Resolution	1920 x 1080 Pixels
	Brightness	250 cd/m²
	Contrast Ratio	1000
	Aspect Ratio	16:9
	Active Area Size (WxH)	579.6 x 336.15mm
	Viewing Angle Touch	85°/85°(H), 80°/80°(V)
	Touch Technology	Capacitive G+G 10 point
Hardware and OS	CPU	RK3288, Cortex-A17, up to 1.8GHz Quad Core
	GPU	Mali T764
	Internal Memory	2GB, DDR3
	Flash Memory	16GB
	Operating System	Android 4.4 / 5.1
	Battery	N/A
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG/JPEG, PNG, BMP
	HDMI Output	HDMI
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	3W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	100M/1000M
	Wireless 3G	Through external USB dongle (optional)
General information	Color	Black (Standard), White (Optional)
	Camera	N/A
	I/O ports	SD, 3.5mm Audio Jack, Mini USB 2.0 OTG x 1, USB 2.0 Host x 2, DC, RJ45
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
	Optional Accessories	Floor stand, Counter Stand
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/4A
	Power Consumption	40W (max)
	Power Over Ethernet	N/A
	Operating Temperature	0-40 °C
	Relative Humidity	85%
	Certification	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	652 x 392 x 36mm
	Product Weight	6.95kg
	Gift Box Size	680 x 501 x 120mm
	Master Carton Size	740 x 515 x 250mm
	Master Carton Weight	18.9kg
	Units per Master Carton	2pcs